NSN 4720-00-807-2733

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-807-2733 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 1.000 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 1.625 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end **Burst Test Pressure:** 1000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 250.0 pounds per square inch **Thread Size:** 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 500.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 80.000 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Un 1st end

Shelf Life:

N/a

NSN 4720-00-807-2733

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0