NSN 4720-00-808-7908

Nonmetallic Hose Assembly - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/4720-00-806-7908
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.977 inches and 1.023 inches
Tempurature Rating:
250.0 degrees fahrenheit single response
Outside Diameter:
Between 1.454 inches and 1.546 inches
Minimum Inside Bending Radius:
11.000 inches
Hose Or Tubing Specification/std Data:
Mil-h-13531, type 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
End Fitting Component And Material:
Nut steel 1st end
Fitting Component And Surface Treatment:
Nut cadmium 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Second End Relationship With First End:
Not identical
Burst Test Pressure:
4000.0 pounds per square inch
First End Swivel Action Capability:
Included
Layer Composition And Location:
Outer layer braided steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch

37.0 degrees 2nd end

1.000 inches 2nd end

Thread Size:

Seat Angle:

NSN 4720-00-808-7908

Nonmetallic Hose Assembly - Page 2 of 2



Hydrostatic Test Pressure:
2000.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Outer Covering Environmental Protection:
Mildew resistant and oil resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
47.500 inches working and 48.500 inches working
Second End Swivel Action Capability:
Not included
Special Features:
Inner conveying tube material-rubber, buna-n
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Un 1st end
Specification Data:
Mil-h-13531, type 1 professional/industrial association specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0
Mil-std (military Standard):

Mil-h-13531 spec.