## NSN 4720-00-809-1574



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-809-1574 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Outside Diameter:** 0.500 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 1250.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and outer layer molded rubber, synthetic

**Maximum Operating Pressure:** 200.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 400.0 pounds per square inch **Outer Covering Environmental Protection:** Abrasion resistant and fuel resistant and oil resistant Vacuum In Torr: 254.0 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 44.000 inches working Media For Which Designed: Air single response **Thread Series Designator:** Unjf 1st end

## NSN 4720-00-809-1574

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ifica	tion	Data:
------	-------	------	-------

88044-an6270 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0