

View Online at <https://aerobasegroup.com/nsn/4720-00-810-3231>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.500 inches

**Temperature Rating:**

-67.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

**Flange Thickness:**

0.315 inches 2nd end

**Outside Diameter:**

0.906 inches

**Minimum Inside Bending Radius:**

7.000 inches

**Flange Outside Diameter:**

1.188 inches 2nd end

**Connection Style:**

Plain w/ gasket groove (sae flanged head) 2nd end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Plain face flange 2nd end

**Burst Test Pressure:**

7000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided steel wire and 2nd layer braided fabric and outer layer molded rubber, chloroprene

**Maximum Operating Pressure:**

200.0 pounds per square inch

**Flow Angle:**

30.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Cold resistant and oil resistant and corrosion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

13.750 inches working

**Flange Style:**

Round w/ out bolt holes 2nd end

**Media For Which Designed:**

Hydraulic fluid single response

**Supplementary Features:**

This item has been reviewed for asbestos material. The current approved sources 11083 have indicated thier part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0