

View Online at <https://aerobasegroup.com/nsn/4720-00-810-3231>

Cross Sectional Shape:

Round

Inside Diameter:

0.500 inches

Temperature Rating:

-67.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Flange Thickness:

0.315 inches 2nd end

Outside Diameter:

0.906 inches

Minimum Inside Bending Radius:

7.000 inches

Flange Outside Diameter:

1.188 inches 2nd end

Connection Style:

Plain w/ gasket groove (sae flanged head) 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

7000.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and 2nd layer braided fabric and outer layer molded rubber, chloroprene

Maximum Operating Pressure:

200.0 pounds per square inch

Flow Angle:

30.0 degrees 2nd end

Outer Covering Environmental Protection:

Cold resistant and oil resistant and corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

13.750 inches working

Flange Style:

Round w/ out bolt holes 2nd end

Media For Which Designed:

Hydraulic fluid single response

Supplementary Features:

This item has been reviewed for asbestos material. The current approved sources 11083 have indicated thier part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0