Nonmetallic Hose Assembly - Page 1 of 2



Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.406 inches	
Outside Diameter:	
0.766 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Thready Qty Per Inch (tpi):	
16 1st end	
Burst Test Pressure:	
8000.0 pounds per square inch	
Layer Composition And Locat	ion:
1st layer braided cotton cord and	2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure	
2000.0 pounds per square inch	
Thread Size:	
0.750 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
4000.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Lengt	1:
26.500 inches working	
Thread Series Designator:	
Unf 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	

No

NSN 4720-00-810-4178

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

