Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-811-7674

| Cross Sectional Shape: |
|--|
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 1.000 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.563 inches |
| Minimum Inside Bending Radius: |
| 12.000 inches |
| Connection Style: |
| Inverted flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external pipe 1st end |
| Features Provided: |
| Reusable end fittings |
| Burst Test Pressure: |
| 8000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 2000.0 pounds per square inch |
| Thread Size: |
| 1.000 inches 1st end |
| Seat Angle: |
| 30.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 4000.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 33.875 inches |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| |

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0