NSN 4720-00-812-1198

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-812-1198 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.406 inches **Outside Diameter:** 0.766 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end **Burst Test Pressure:** 8000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord **Maximum Operating Pressure:** 2000.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 4000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 64.000 inches working **Thread Series Designator:** Unf 1st end Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 4720-00-812-1198

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0