Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-812-7760

view Online at https://deiobasegroup.com/hsh/4/20-00-012-1/00
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.734 inches
Minimum Inside Bending Radius:
1.750 inches
Exterior Color:
Black
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
1250.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
2500.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
24.000 inches
Media For Which Designed:
Fuel/ail bydraearban single rasponse

Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2

Thread Series Designator:

Unf 1st end

Specification Or Standard:

3 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

