

View Online at <https://aerobasegroup.com/nsn/4720-00-812-8590>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.359 inches and 0.391 inches

Temperature Rating:

-40.0 degrees celsius and 93.3 degrees celsius single response

Outside Diameter:

Between 0.734 inches and 0.766 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

4500.0 pounds per square inch

Layer Composition And Location:

1st layer spirally laid rayon cord and 2nd layer spirally laid rayon cord and outer layer molded rubber, synthetic

Maximum Operating Pressure:

1125.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2250.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

43.000 inches working

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0