

View Online at <https://aerobasegroup.com/nsn/4720-00-812-8595>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

Between 0.359 inches and 0.391 inches

**Temperature Rating:**

-40.0 degrees celsius and 93.3 degrees celsius single response

**Outside Diameter:**

Between 0.734 inches and 0.766 inches

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

4500.0 pounds per square inch

**Layer Composition And Location:**

1st layer spirally laid cotton cord and 2nd layer spirally laid cotton cord and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

1125.0 pounds per square inch

**Thread Size:**

0.562 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

2250.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

48.000 inches working

**Media For Which Designed:**

Hydraulic fluid, phosphate-ester base single response

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0