## NSN 4720-00-814-1722

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-814-1722

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.219 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.438 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
20 2nd end
Burst Test Pressure:
Burst Test Pressure: 6000.0 pounds per square inch
6000.0 pounds per square inch
6000.0 pounds per square inch  Layer Composition And Location:
6000.0 pounds per square inch  Layer Composition And Location:  1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire
6000.0 pounds per square inch  Layer Composition And Location:  1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:
6000.0 pounds per square inch  Layer Composition And Location:  1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1500.0 pounds per square inch
6000.0 pounds per square inch  Layer Composition And Location:  1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:
6000.0 pounds per square inch  Layer Composition And Location:  1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.438 inches 1st end
6000.0 pounds per square inch  Layer Composition And Location:  1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.438 inches 1st end  Seat Angle:
6000.0 pounds per square inch  Layer Composition And Location:  1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.438 inches 1st end  Seat Angle:  37.0 degrees 2nd end
6000.0 pounds per square inch  Layer Composition And Location:  1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.438 inches 1st end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:
6000.0 pounds per square inch  Layer Composition And Location:  1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.438 inches 1st end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch
6000.0 pounds per square inch  Layer Composition And Location:  1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.438 inches 1st end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Flow Angle:
6000.0 pounds per square inch  Layer Composition And Location:  1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.438 inches 1st end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Flow Angle:  90.0 degrees 2nd end
6000.0 pounds per square inch  Layer Composition And Location:  1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.438 inches 1st end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Flow Angle:  90.0 degrees 2nd end  Outer Covering Environmental Protection:

22.000 inches working

**Measuring Method And Length:** 

## NSN 4720-00-814-1722

Nonmetallic Hose Assembly - Page 2 of 2



	•	
I hread	Series	Designator:

Unf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0