NSN 4720-00-814-2540

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-814-2540

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.410 inches
Connection Style:
Swivel nut with compression sleeve 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
12.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
9.750 inches working
Thread Series Designator:
Unf 2nd end
Shelf Life:

NSN 4720-00-814-2540

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0