NSN 4720-00-814-2542

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-814-2542

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.329 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response
Outside Diameter:
0.620 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
1st layer spirally laid steel wire and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
12.000 inches
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a

NSN 4720-00-814-2542

Nonmetallic Hose Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0