NSN 4720-00-814-2546

Unjf 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-814-2546

Cross Sectional Shape:					
Round					
Thread Class:					
3b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.229 inches					
Tempurature Rating:					
-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response					
Outside Diameter:					
0.415 inches					
Minimum Inside Bending Radius:					
3.000 inches					
Connection Style:					
Swivel nut with compression sleeve 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Features Provided:					
Electrostatic discharge capability					
Burst Test Pressure:					
16000.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire					
Maximum Operating Pressure:					
3000.0 pounds per square inch					
Thread Size:					
0.438 inches 1st end					
Seat Angle:					
37.0 degrees 1st end					
Hydrostatic Test Pressure:					
6000.0 pounds per square inch					
Outer Covering Environmental Protection:					
Corrosion resistant					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
18.500 inches working					
Thread Series Designator:					

NSN 4720-00-814-2546

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	.1+		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0