

View Online at <https://aerobasegroup.com/nsn/4720-00-815-3522>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.590 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Exterior Color:**

Black

**Connection Style:**

Inverted flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded external pipe 1st end

**Burst Test Pressure:**

4500.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided fabric and 2nd layer braided fabric and outer layer molded rubber, chloroprene

**Maximum Operating Pressure:**

1125.0 pounds per square inch

**Thread Size:**

0.250 inches 1st end

**Seat Angle:**

30.0 degrees 1st end

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Corrosion resistant and mildew resistant and ozone resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

16.500 inches

**Media For Which Designed:**

Hydraulic fluid single response

**Thread Series Designator:**

Nptf 1st end

**Specification Data:**

81349-mil-h-13719 government specification

**Specification Or Standard:**

1 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0

**Mil-std (military Standard):**

Mil-h-13719 spec.