

View Online at <https://aerobasegroup.com/nsn/4720-00-817-9335>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.438 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.859 inches

**Minimum Inside Bending Radius:**

5.750 inches

**Connection Style:**

Swivel nut with loose or integral clinch sleeve 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

14000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

12.0 degrees 1st end

**Hydrostatic Test Pressure:**

7000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Abrasion resistant and oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

54.000 inches working

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unf 1st end

**Specification Data:**

96906-ms28762 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0