

View Online at <https://aerobasegroup.com/nsn/4720-00-819-1999>

Cross Sectional Shape:

Round

Inside Diameter:

0.615 inches

Temperature Rating:

-67.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

Bolt Circle Diameter:

1.156 inches 1st end

Flange Thickness:

0.297 inches 1st end

Outside Diameter:

0.812 inches

Minimum Inside Bending Radius:

6.500 inches

Exterior Color:

Natural

Angle Between Rigid Elbow Fittings In Deg:

320.0

Bolt Hole Quantity:

4 2nd end

Flange Outside Diameter:

2.094 inches 1st end

Connection Style:

Plain 1st end

Bolt Hole Diameter:

0.205 inches 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Plain face flange 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

3500.0 pounds per square inch

Layer Composition And Location:

Outer layer braided steel wire

Maximum Operating Pressure:

1000.0 pounds per square inch

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Flow Angle:

45.0 degrees 1st end

Outer Covering Environmental Protection:

Corrosion resistant and fuel resistant and salt water resistant and weatherproof

Vacuum In Torr:

254.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

26.000 inches working

Special Features:

Polytetrafluoroethylene chafe sleeves, 2.25 in. Lg on both ends

Specification Data:

81349-milh25579 government specification

Specification Or Standard:

1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-25579 spec.