

View Online at <https://aerobasegroup.com/nsn/4720-00-819-5370>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

1.375 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response

**Flange Thickness:**

0.375 inches 2nd end

**Outside Diameter:**

1.672 inches

**Minimum Inside Bending Radius:**

10.500 inches

**Center To Center Distance Between Bolt Holes Along Width:**

1.800 inches 2nd end

**Center To Center Distance Between Bolt Holes Along Length:**

1.800 inches 2nd end

**Bolt Hole Quantity:**

4 2nd end

**Flange Length:**

2.400 inches 2nd end

**Flange Width:**

2.400 inches 2nd end

**Connection Style:**

Raised swivel 2nd end

**Bolt Hole Diameter:**

0.275 inches 2nd end

**Raised Face Height:**

0.020 inches 2nd end

**Raised Face Diameter:**

2.121 inches 2nd end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Raised face flange 2nd end

**Burst Test Pressure:**

4000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1000.0 pounds per square inch

**Hydrostatic Test Pressure:**

2000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Corrosion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

17.000 inches working

**Flange Style:**

Rectangular (includes square) 2nd end

**Supplementary Features:**

This item has been reviewed for asbestos material. The current approved source, 50599, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0