

View Online at <https://aerobasegroup.com/nsn/4720-00-819-5370>

Cross Sectional Shape:

Round

Inside Diameter:

1.375 inches

Temperature Rating:

-65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response

Flange Thickness:

0.375 inches 2nd end

Outside Diameter:

1.672 inches

Minimum Inside Bending Radius:

10.500 inches

Center To Center Distance Between Bolt Holes Along Width:

1.800 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.800 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.400 inches 2nd end

Flange Width:

2.400 inches 2nd end

Connection Style:

Raised swivel 2nd end

Bolt Hole Diameter:

0.275 inches 2nd end

Raised Face Height:

0.020 inches 2nd end

Raised Face Diameter:

2.121 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Raised face flange 2nd end

Burst Test Pressure:

4000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1000.0 pounds per square inch

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

17.000 inches working

Flange Style:

Rectangular (includes square) 2nd end

Supplementary Features:

This item has been reviewed for asbestos material. The current approved source, 50599, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0