## NSN 4720-00-820-0706



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-820-0706 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** Between 0.899 inches and 0.945 inches **Minimum Inside Bending Radius:** 5.500 inches **Connection Style:** Inverted flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external pipe 1st end **Burst Test Pressure:** 7000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric **Maximum Operating Pressure:** 1750.0 pounds per square inch **Thread Size:** 0.500 inches 1st end Seat Angle: 30.0 degrees 1st end **Hydrostatic Test Pressure:** 3500.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 44.500 inches **Thread Series Designator:** Nptf 1st end Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 4720-00-820-0706

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0