

View Online at <https://aerobasegroup.com/nsn/4720-00-820-3076>

Cross Sectional Shape:

Round

Thread Class:

2b 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.875 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

1.234 inches

Minimum Inside Bending Radius:

7.375 inches

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 2nd end

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

3200.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and 2nd layer wrapped rubber, natural and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

800.0 pounds per square inch

Thread Size:

1.000 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

1600.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and water resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

52.400 inches random and 52.850 inches random

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0