NSN 4720-00-820-8656

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-820-8656

Cross Sectional Shape:
Round
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 158.0 degrees fahrenheit single response
Outside Diameter:
0.453 inches
Quick Disconnect Size:
0.250 inches 1st end
Connection Style:
Cam or lever (external) 1st end
End Connection Design:
Straight 1st end
Connection Type:
External quick disconnect 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
3000.0 pounds per square inch
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Water resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
144.000 inches excluding end fittings
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A542a0