Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-821-0772

View Online at https://aerobasegroup.com/nsn/4720-00-821-0772	
Cross Sectional Shape:	
Round	
Fhread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
nside Diameter:	
0.438 inches	
Tempurature Rating:	
65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response	
Dutside Diameter:	
0.659 inches	
Connection Style:	
Swivel nut, flareless 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Fhready Qty Per Inch (tpi):	
16 1st end	
Burst Test Pressure:	
14000.0 pounds per square inch	
_ayer Composition And Location:	
1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, s	synthetic
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.750 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
7000.0 pounds per square inch	
Duter Covering Environmental Protection:	
Abrasion resistant and fuel resistant and oil resistant and ozone resistant and cold resistant	
nside Surface Condition:	
Smooth	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Fhread Series Designator:	
Jnf 1st end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0