

View Online at <https://aerobasegroup.com/nsn/4720-00-821-5541>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Outside Diameter:

0.390 inches

Minimum Inside Bending Radius:

2.000 inches

Inner Conveying Tube Style:

Helical open-pitch corrugated

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

7200.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1800.0 pounds per square inch

Thread Size:

0.500 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

3600.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Measuring Method And Length:

10.000 inches working

Thread Series Designator:

Unjf 1st end

Specification Data:

36659-751352-1 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A542a0