Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-826-8802

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.219 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and	d 200.0 degrees fahrenheit single response
Outside Diameter:	
0.625 inches	
Connection Style:	
Swivel nut with loose or integ	ral clinch sleeve 1st end
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st er	nd
Thready Qty Per Inch (tpi):	
20 1st end	
Burst Test Pressure:	
16000.0 pounds per square i	nch
Layer Composition And Lo	cation:
1st layer braided corrosion re	esistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber,
chloroprene	
Maximum Operating Press	ure:
3000.0 pounds per square in	ch
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
12.0 degrees 1st end	
Hydrostatic Test Pressure:	
8000.0 pounds per square in	ch
Outer Covering Environme	ntal Protection:
Abrasion resistant and oil res	sistant
Inside Surface Condition:	
Smooth	
Media For Which Designed	:
Air and fuel/oil, hydrocarbor	n single response
Thread Series Designator:	
Unf 1st end	
Shelf Life:	
N/a	
Shelf Life:	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0