NSN 4720-00-828-2152

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-828-2152

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.400 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.650 inches |
| Minimum Inside Bending Radius: |
| 5.750 inches |
| Connection Style: |
| Swivel nut with compression sleeve 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Electrostatic discharge capability |
| Thready Qty Per Inch (tpi): |
| 16 1st end |
| Burst Test Pressure: |
| 14000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 1st end |
| Seat Angle: |
| 12.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 6000.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 24.500 inches working |

Special Features:

With polytetrafluroethylene shafe guard

NSN 4720-00-828-2152

Nonmetallic Hose Assembly - Page 2 of 2



| Thread Series Designator | tor: |
|--------------------------|------|
|--------------------------|------|

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0