NSN 4720-00-830-0737

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-830-0737

Inside Diameter:			
0.188 inches			
Tempurature Rating:			
-67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response			
Outside Diameter:			
0.388 inches			
Minimum Inside Bending Radius:			
2.000 inches			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Features Provided:			
Electrostatic discharge capability			
Burst Test Pressure:			
12000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
1500.0 pounds per square inch			
Thread Size:			
0.438 inches 1st end			
Seat Angle:			
37.0 degrees 1st end			
Hydrostatic Test Pressure:			
3000.0 pounds per square inch			
Outer Covering Environmental Protection:			
Corrosion resistant			
Vacuum In Torr:			
50.8			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
7.500 inches working			

NSN 4720-00-830-0737

Nonmetallic Hose Assembly - Page 2 of 2



		_
Thread	l Series	Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0