## NSN 4720-00-831-5347

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-831-5347

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.438 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response
Outside Diameter:
0.688 inches
Minimum Inside Bending Radius:
5.750 inches
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Seat Angle:
12.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
22.000 inches working
Thread Series Designator:

Unf 2nd end

## NSN 4720-00-831-5347

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0