Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-831-8248

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.688 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut, gasket seal 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal hose 2nd end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and outer layer molded rubber, synthetic
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
1.000 inches 2nd end
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
73.000 inches working
Media For Which Designed:
Water single response
Thread Series Designator:
Npsh 2nd end
Shelf Life:
N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0