Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-831-8254
Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.480 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and outer layer braided textile yarn
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and oil resistant
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 28.750 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A542a0