

View Online at <https://aerobasegroup.com/nsn/4720-00-831-8300>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.212 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

**Outside Diameter:**

0.507 inches

**Minimum Inside Bending Radius:**

3.000 inches

**Exterior Color:**

Natural

**Hose Or Tubing Specification/std Data:**

Mil-h-38360, size 4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Connection Style:**

Swivel nut, flareless 2nd end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting stainless steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting passivate 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

16000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire err-100

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**External Protection Type And Location (non-core):**

chafe guard, spirally wrapped polytetrafluoroethylene

**Seat Angle:**

12.0 degrees 2nd end

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Corrosion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

29.000 inches working

**Second End Swivel Action Capability:**

Not included

**Special Features:**

External protection type and location- chafe guard, spirally wrapped polytetrafluoroethylene , inner conveying tube material-plastic, polytetrafluoroethylene

**Media For Which Designed:**

Air single response and hydraulic fluid single response

**Thread Series Designator:**

Unjf 1st end

**Specification Data:**

81349-mil-h-38360 government specification

**Specification Or Standard:**

4 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0

**Mil-std (military Standard):**

Mil-h-38360 spec.