## NSN 4720-00-832-7160

Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-00-832-7160 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 1.000 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 1.500 inches **Minimum Inside Bending Radius:** 12.000 inches **Connection Style:** Inverted flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external pipe 1st end **Burst Test Pressure:** 8000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 2000.0 pounds per square inch **Thread Size:** 1.000 inches 1st end Seat Angle: 30.0 degrees 1st end **Hydrostatic Test Pressure:** 4000.0 pounds per square inch **Outer Covering Environmental Protection:** Mildew resistant and oil resistant and oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 71.250 inches and 72.750 inches Media For Which Designed: Hydraulic fluid single response **Thread Series Designator:** Npt 1st end

Shelf Life:

N/a

## NSN 4720-00-832-7160

Nonmetallic Hose Assembly - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0