NSN 4720-00-832-7166

Cross Sectional Shape:

Round

Thread Class: 2a 1st end

Thread Direction:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-832-7166

Right-hand 1st end					
Inside Diameter:					
1.000 inches					
Tempurature Rating:					
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response					
Outside Diameter:					
1.562 inches					
Minimum Inside Bending Radius:					
11.000 inches					
Connection Style:					
Inverted flare 2nd end					
End Connection Design:					
Straight 2nd end					
Connection Type:					
Threaded external tube 1st end					
Thready Qty Per Inch (tpi):					
16 1st end					
Burst Test Pressure:					
8000.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided steel wire and outer layer molded rubber					
Maximum Operating Pressure:					
2000.0 pounds per square inch					
Thread Size:					
1.000 inches 2nd end					
Seat Angle:					
30.0 degrees 2nd end					
Hydrostatic Test Pressure:					
4000.0 pounds per square inch					
Outer Covering Environmental Protection:					
Mildew resistant and oil resistant and oil resistant					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
151.000 inches					
Media For Which Designed:					

Fuel/oil, hydrocarbon single response

NSN 4720-00-832-7166

Nonmetallic Hose Assembly - Page 2 of 2



Th		Carias	Dania	
111	ıeau	Series	Desid	mator.

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0