NSN 4720-00-832-7168

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-832-7168

Cross Sectional Shape:				
Round				
Thread Class:				
2a 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
1.000 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter:				
1.500 inches				
Minimum Inside Bending Radius:				
11.000 inches				
Connection Style:				
Inverted flare 2nd end				
End Connection Design:				
Straight 2nd end				
Connection Type:				
Threaded external tube 1st end				
Features Provided:				
Electrostatic discharge capability				
Thready Qty Per Inch (tpi):				
16 1st end				
Burst Test Pressure:				
8000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene				
Maximum Operating Pressure:				
2000.0 pounds per square inch				
Thread Size:				
1.000 inches 2nd end				
Seat Angle:				
30.0 degrees 2nd end				
Hydrostatic Test Pressure:				
4000.0 pounds per square inch				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
31.000 inches				
Media For Which Designed:				

Fuel/oil, hydrocarbon single response

NSN 4720-00-832-7168

Nonmetallic Hose Assembly - Page 2 of 2



T	hread	Series	Desi	ignator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0