## NSN 4720-00-832-7853

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-832-7853

Cross Sectional Shape:
Round
Fhread Direction:
Right-hand 1st end
nside Diameter:
1.000 inches
Fempurature Rating:
42.0 degrees fahrenheit and 100.0 degrees fahrenheit single response
Outside Diameter:
1.625 inches
Exterior Color:
Black
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Fhreaded internal pipe 1st end
Thready Qty Per Inch (tpi):
11-1/2 1st end
Burst Test Pressure:
500.0 pounds per square inch
Layer Composition And Location:
Ist layer rubber impregnated braided cotton cord and 2nd layer braided copper wire and outer layer molded rubber, synthetic  Fhread Size:
1.000 inches 2nd end
Hydrostatic Test Pressure:
150.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and oil resistant and mildew resistant and cold resistant
nside Surface Condition:
Smooth
Measuring Method And Length:
120.000 inches excluding end fittings
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Npt 2nd end
Shelf Life:
V/a Init Of Measure:

--

## NSN 4720-00-832-7853

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0