## NSN 4720-00-834-1673



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-834-1673 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.688 inches **Minimum Inside Bending Radius:** 5.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 2250.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 4500.0 pounds per square inch **Outer Covering Environmental Protection:** 

## Oil resistant and ozone resistant **Inside Surface Condition:** Smooth

**Measuring Method And Length:** 

32.188 inches

## NSN 4720-00-834-1673

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designe	Which Designe	ed
-------------------------	---------------	----

Fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0