NSN 4720-00-834-1706

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-834-1706 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.382 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.781 inches **Minimum Inside Bending Radius:** 4.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 2250.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 4500.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 21.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

NSN 4720-00-834-1706

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0