NSN 4720-00-834-2659

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.212 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-834-2659

| Tempurature Rating: | | | | |
|---|--|--|--|--|
| -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response | | | | |
| Outside Diameter: | | | | |
| Between 0.360 inches and 0.390 inches | | | | |
| Minimum Inside Bending Radius: | | | | |
| 1.500 inches | | | | |
| Connection Style: | | | | |
| Swivel nut, flareless 1st end | | | | |
| End Connection Design: | | | | |
| Straight 1st end | | | | |
| Connection Type: | | | | |
| Threaded internal tube 1st end | | | | |
| Burst Test Pressure: | | | | |
| 12000.0 pounds per square inch | | | | |
| Layer Composition And Location: | | | | |
| Outer layer braided corrosion resistant steel wire | | | | |
| Maximum Operating Pressure: | | | | |
| 3000.0 pounds per square inch | | | | |
| Thread Size: | | | | |
| 0.438 inches 1st end | | | | |
| Seat Angle: | | | | |
| 12.0 degrees 1st end | | | | |
| Hydrostatic Test Pressure: | | | | |
| 6000.0 pounds per square inch | | | | |
| Outer Covering Environmental Protection: | | | | |
| Heat resistant and vibration resistant | | | | |
| Inside Surface Condition: | | | | |
| Smooth | | | | |
| Measuring Method And Length: | | | | |
| 16.250 inches working | | | | |
| Thread Series Designator: | | | | |
| Unjf 1st end | | | | |
| Specification Data: | | | | |
| 81343-as115 professional/industrial association standard | | | | |

NSN 4720-00-834-2659

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | | |
|---|----|------|---|------|
| c | hο | JIF. | | ife: |
| J | | | _ | HG. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0