NSN 4720-00-836-4104

Cross Sectional Shape:

Inside Diameter: 1.500 inches

Round

Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-836-4104

| Tempurature Rating: | | | | | | | |
|--|--|--|--|--|--|--|--|
| 150.0 degrees fahrenheit single response | | | | | | | |
| Bolt Circle Diameter: | | | | | | | |
| 3.750 inches 1st end | | | | | | | |
| Flange Thickness: | | | | | | | |
| 1.642 inches 1st end | | | | | | | |
| Outside Diameter: | | | | | | | |
| 1.685 inches | | | | | | | |
| Inner Conveying Tube Style: | | | | | | | |
| Annular close-pitch corrugated | | | | | | | |
| Bolt Hole Quantity: | | | | | | | |
| 6 1st end | | | | | | | |
| Flange Outside Diameter: | | | | | | | |
| 5.375 inches 1st end | | | | | | | |
| Connection Style: | | | | | | | |
| Plain 1st end | | | | | | | |
| Bolt Hole Diameter: | | | | | | | |
| 0.750 inches 1st end | | | | | | | |
| End Flange Construction: | | | | | | | |
| Solid 1st end | | | | | | | |
| End Connection Design: | | | | | | | |
| Straight 1st end | | | | | | | |
| Connection Type: | | | | | | | |
| Plain face flange 1st end | | | | | | | |
| Features Provided: | | | | | | | |
| Identical ends | | | | | | | |
| Layer Composition And Location: | | | | | | | |
| Outer layer braided nickel copper alloy wire err-100 | | | | | | | |
| Maximum Operating Pressure: | | | | | | | |
| 700.0 pounds per square inch | | | | | | | |
| Measuring Method And Length: | | | | | | | |
| 37.000 inches working | | | | | | | |
| Flange Style: | | | | | | | |
| Round w/ bolt holes 1st end | | | | | | | |
| Special Features: | | | | | | | |
| 90 degrees elbow located 18.500 in. From first end | | | | | | | |
| Shelf Life: | | | | | | | |
| Official Elife. | | | | | | | |

NSN 4720-00-836-4104

Metallic Hose Assembly - Page 2 of 2



| | | eas | |
|--|--|-----|--|

--

Demilitarization:

No

Fiig:

A542a0