## NSN 4720-00-836-7556

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-836-7556

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-67.0 degrees fahrenheit single response and 158.0 degrees fahrenheit single response
Outside Diameter:
0.438 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting aluminum alloy all ends
Connection Type:
Threaded internal tube 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
1700.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer molded rubber, synthetic err-100
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Vacuum In Torr:
254.0
Inside Surface Condition:
Smooth
Measuring Method And Length:
6.000 inches working

## NSN 4720-00-836-7556

Nonmetallic Hose Assembly - Page 2 of 2



Special	Features:
---------	-----------

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Unf 1st end

**Specification Data:** 

88044-an6270 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0