Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-837-7878

Cross Sectional Shaney
Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.780 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
2250.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
4500.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
25.500 inches
Media For Which Designed:
Grease and fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
iwa

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0