## NSN 4720-00-839-3267



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-839-3267 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.750 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 1.031 inches **Minimum Inside Bending Radius:** 7.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 14 1st end **Burst Test Pressure:** 1000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided rayon cord and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 250.0 pounds per square inch **Thread Size:** 1.062 inches 1st end Seat Angle: 45.0 degrees 1st end Vacuum In Torr: 304.8 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 21.000 inches excluding end fittings **Thread Series Designator:** Uns 1st end

Shelf Life:

N/a

## NSN 4720-00-839-3267

Nonmetallic Hose Assembly - Page 2 of 2



| ı | In | it I | Of | · M | دما | e i | ıre: |
|---|----|------|----|-----|-----|-----|------|
| ι | JΝ | II ' | ωı | IV  | еа  | SU  | ıre: |

--

Demilitarization:

No

Fiig:

A542a0