NSN 4720-00-839-5177

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-839-5177 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.875 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Minimum Inside Bending Radius: 7.380 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end **Burst Test Pressure:** 3200.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord **Maximum Operating Pressure:** 800.0 pounds per square inch **Thread Size:** 1.000 inches 2nd end Seat Angle: 37.0 degrees 2nd end **Hydrostatic Test Pressure:** 1600.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 48.000 inches **Thread Series Designator:** Un 1st end Shelf Life: N/a

Unit Of Measure:

NSN 4720-00-839-5177

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0