## NSN 4720-00-842-4944

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-842-4944

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
Outside Diameter:
Between 0.297 inches and 0.344 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Gray or natural
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nuts drilled for lockwire
Thready Qty Per Inch (tpi):
20 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant

## NSN 4720-00-842-4944

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
8.625 inches working and 8.875 inches working
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A542a0