

View Online at <https://aerobasegroup.com/nsn/4720-00-844-0389>

Cross Sectional Shape:

Round

Thread Class:

2b 2nd end and 2a 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.125 inches

Exterior Color:

Black

Hose Or Tubing Specification/std Data:

Saej1401-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Inverted flare 2nd end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded internal and external tube 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

2500.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer rubber impregnated braided cotton cord err-100 or 1st layer rubber impregnated braided rayon cord err-100

Thread Size:

0.437 inches 2nd end and 0.562 inches 2nd end

Seat Angle:

37.0 degrees 1st end

Outer Covering Environmental Protection:

Weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

27.500 inches

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end and unf 2nd end

Specification Data:

Saej1401-81343 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0