Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-844-3466

0	an Constituted Shares
Rou	es Sectional Shape:
	ead Class:
	st end
	ad Direction:
-	t-hand 1st end de Diameter:
	8 inches
	purature Rating:
) degrees fahrenheit single response and 450.0 degrees fahrenheit single response
	side Diameter:
	2 inches
	mum Inside Bending Radius:
	0 inches
	le Between Rigid Elbow Fittings In Deg:
90.0	
	nection Style:
	rel nut flare 1st end
	Connection Design:
	w 1st end
	nection Type:
	aded internal tube 1st end
	ures Provided:
	trostatic discharge capability
	st Test Pressure:
1200	00.0 pounds per square inch
	er Composition And Location:
-	er layer braided corrosion resistant steel wire
	imum Operating Pressure:
1500	0.0 pounds per square inch
Thre	ad Size:
0.43	8 inches 1st end
Seat	Angle:
37.0	degrees 1st end
Hyd	rostatic Test Pressure:
3000	0.0 pounds per square inch
Flow	/ Angle:
90.0	degrees 1st end
Insid	de Surface Condition:
Smo	oth
Mea	suring Method And Length:
15.0	00 inches working

Nonmetallic Hose Assembly - Page 2 of 2

Thread Series Designator:

Unf 1st end

Specification Or Standard:

1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

