NSN 4720-00-844-7539

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-844-7539

Cross Sectional Shape:
Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.750 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut, inverted flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external tube 2nd end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided synthetic cord and outer layer molded rubber, synthetic
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
0.625 inches 1st end
Seat Angle:
45.0 degrees 2nd end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
23.000 inches
Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-00-844-7539

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0