## NSN 4720-00-845-0515



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-845-0515 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.188 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.484 inches **Minimum Inside Bending Radius:** 2.000 inches **Connection Style:** Swivel nut, flareless 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 3000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated cotton fabric **Maximum Operating Pressure:** 1500.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end **Hydrostatic Test Pressure:** 3000.0 pounds per square inch **Outer Covering Environmental Protection:** 

Oil resistant

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

45.000 inches working

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

## NSN 4720-00-845-0515

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0