NSN 4720-00-845-9006

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-845-9006 **Cross Sectional Shape:** Round **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.750 inches **Minimum Inside Bending Radius:** 4.000 inches **Exterior Color:** Black Angle Between Rigid Elbow Fittings In Deg: 90.0 **Connection Style:** Swivel nut, inverted flare 1st end **End Connection Design:** Elbow 1st end **Connection Type:** Threaded external tube 1st end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.625 inches 1st end Seat Angle: 45.0 degrees 1st end **Hydrostatic Test Pressure:** 6000.0 pounds per square inch Flow Angle: 90.0 degrees 1st end **Inside Surface Condition:**

Smooth

Measuring Method And Length:

21.500 inches

NSN 4720-00-845-9006

Nonmetallic Hose Assembly - Page 2 of 2



N	Λ	edia	For	Which	Design	ed

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0